

## Self-drilling screw JT3-ST-2-6.0




### Application range

- > Fastening rail systems with intermediate insulation to thin-walled steel, aluminium or timber substructure
- > Fastening timber components to thin-walled steel or aluminium substructure
- > To fix roofing membranes and insulating material to substructures made of sheet steel  $\geq 0.70 \text{ mm} \leq 1.5 \text{ mm}$ , timber or wood-based material in combination with EJOT stress plates


### Properties

- > A2 stainless steel with hardened steel drill point
- > With countersunk head

### Applications




### Technical specifications



### Cross references

Bit hexalobular TX25  
 Bit holder  
 Cordless screwdriver ASCS 6.3  
 Flat roof profile FP  
 Stress plate EcoTek 50  
 Stress plate EcoTek T 50

### Certifications



### Product online



Order description	Length [mm]	Thread length [mm]	Clamping thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT3-ST-2-6.0x35	35	35	0–20	500		7382160301	4061245014104
JT3-ST-2-6.0x60	60	45	15–45	250		7382125301	4061245014111
JT3-ST-2-6.0x80	80	65	15–65	250		7382107301	4061245014128
JT3-ST-2-6.0x100	100	65	35–85	250		7382101301	4061245014180
JT3-ST-2-6.0x120	120	65	55–105	250		7382102301	4061245014173
JT3-ST-2-6.0x140	140	65	75–125	250		7382103301	4061245014166

Further lengths  
 available upon request

